

## CCRGA Spring Rewind, High Capacity, Welding Reels

CCRGA – OXY-ACETYLENE / OXY-PROPANE (200PSI)

Introducing the new high visibility, high capacity series welding reels. Constructed in heavy gauge powder coated steel, offering strength performance and reliability. Capacities of 20m and 30m for either oxy-acetylene or oxy-propane gas applications.

### FEATURES:

- Twin pedestal supports
- Heavy Gauge, all steel construction
- Durable, yellow powder coated finish
- Full flow swivel assemblies for maximum product delivery
- Swept riser assembly for easy hose installation
- Fitted with viton seals as standard
- Large four-way roller guide to reduce hose wear
- Supplied as bare reel, hose at extra cost
- Externally mounted spring canister and swivel assemblies for easy maintenance
- 2-year manufacturers warranty.



| Model Reference | I.D. | O.D. | Max PSI | Swivel In/Out | Reel Dimensions |        |        | Length |
|-----------------|------|------|---------|---------------|-----------------|--------|--------|--------|
|                 |      |      |         |               | W               | H      | D      |        |
| CCRGA-820       | 3/8" | 5/8" | 200     | 2" x 3/8"M    | 385 mm          | 485 mm | 498 mm | 20 m   |
| CCRGA-830       | 3/8" | 5/8" | 200     | 5/8"          | 385 mm          | 540 mm | 520 mm | 30 m   |